

KNAUF

Knauf Fill & Finish Light

Knauf Fill & Finish Light is a lightweight ready-mixed compound for bedding tapes and finishing joints in drywall partitions and ceilings. Delivers up to a Q4 finish.

Product-Data-Sheet



Areas of Application

Gypsum plasterboards, for bedding paper tape and finishing second and third coat of joints. For bedding paper-faced and metal corner beads and finishing joints.

Compliance Standards

EN13963. Type 3A

Key Benefits

- Very low shrinkage finish
- Easy to sand
- Suitable for use with bazooka and banjo machine application
- Tub made from recycled plastic
- Can be used for full surface skim finishing

Build on us.

Creation Date: 08/06/2023
Revision Reference: 002
Revision Date: 04/03/2025

Performance Data

| Reaction to Fire (R2F) | Flexural Strength (F) | Density (g/cm ³) | Dangerous Substances (DS) |
|------------------------|-----------------------|------------------------------|---------------------------|
| A2-s1,d0 | pass (>320 N) | 1.1 – 1.4 | NPD |

Technical Information

| Colour | Weight (kg) | Approximate Coverage | Material Number |
|-------------------|-------------|----------------------|-----------------|
| Light cream/white | 20 | 45 per 20kg tub | 601440 |
| Light cream/white | 5 | 11.25 per 5kg tub | 601462 |

*Based on filling application to tapered edge board

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

< 0.1% (<1 g/L).

Storage and Handling

Store in a well-ventilated place. Keep away from heat and ignition sources. Protect from freezing, high temperatures and direct exposure to sunlight. Not to be used under 5° air or surface temperatures.

Packaging

Recycled content plastic tub. Recyclable at the end of its life. Packed on a wooden pallet with PE shrink wrap.

Shelf Life/Service Life

12 months from the date of production, which is printed on the tub.

Disposal/Repair

Dispose of contents/container in accordance with licensed collectors sorting instructions. 17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02, and 17 09 03.

Health & Safety

Ensure good ventilation, and wear personal protective equipment according to your risk assessment, see safety data sheet. Wear safety glasses with side shields due to splashing. When sanding, wear protective P2 dust mask. Impermeable protective gloves are recommended. Do not eat, drink or smoke when using this product. Always wash hands after handling.

Application / Installation

Stir to an even consistency before use, may be diluted to suit individual preferences. Ensure substrate is sound, dry, clean and free from oil, and dust. Drying time dependent upon thickness, temperature, ventilation, air humidity and type of substrate. Average drying time approximately 12–24 hours. Use a fine-grit sandpaper for surface sanding. Before application of paint or wallpaper, use an appropriate primer such as Knauf Wallboard Primer.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

Datasheet for indoor air quality available on request.

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)
Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 08/06/2023
Revision Reference: 002
Revision Date: 04/03/2025