

# Technical Data Sheet: **RIDGE ROLL**

## **ECO ROLL**



### Product Details

RREC01

Eco roll - this is the sealing-ventilation tape to be used on sloping and level roof ridges.

The PP geo-textile used in that kind of tape with UV stabilising up to 6 months is a very highly specialist raw material, which ensures double protection: water tightness and proper water vapour removal.

The central flat "spine" of the roll is reinforced for fixing to the ridge batten. The two corrugated side flaps are designed to drape down over the top row of tiles on either side as the roll is opened out. The underside has a strip of self-adhesive butyl protected by an easy-release backing tape.



### Features & Benefits

Code:	RREC01
Width:	310mm
Aluminium thickness:	140 $\mu$
UV stabilisation:	Yes
Material:	polyethylene (PE)
Air permeability:	270 g/m <sup>2</sup>
Width butyl glue:	15 mm + / - 1 mm
Thickness butyl glue:	1.5 mm + / - 1 mm
Min. installation temp.:	+ 5 ° C
Temp. resistance:	- 30 ° C to + 80 ° C



**Kytun**<sup>™</sup>  
DRY ROOFING PRODUCTS

Brook House  
Stock Lane  
Halifax  
West Yorkshire  
HX2 7RU

T: +44 (0) 1684 293702  
E: [info@kytun.com](mailto:info@kytun.com)  
W: [www.kytun.com](http://www.kytun.com)

For a full list of products visit us on:  
**[www.kytun.com](http://www.kytun.com)**