



Elvion Home Water Kit

MANUAL





Content

Inline Installation 4


Cartridge replacement 6

Home Water Kit

Inline Installation

1


Turn off the water inlet/shut-off valve, which is generally fitted on the mains cold water supply under the kitchen sink. Turn on the cold side of the tap to drain all remaining water from the pipework.



2

Disconnect the pipework on the cold water side of the tap and install the included flexibles on the cold water line pipework. Take care of the residual water that could come from the existing pipework. Where necessary, use PTFE Tape to secure connections.


CAUTION: Do not connect the filter on the hot water line.



3


Mount the delivered head onto the wall or inside panel of under-sink unit. Make sure to have enough available space for the installation of the cartridge.

NOTE: By default, the In and Out of the head are on the right side. Depending on your installation and future changing, you can detach the top piece by unscrewing the 4 screws on the bottom and turn it around to have the IN and OUT on the left side.




4

Connect the delivered flexibles to the head, push the stem of the flexible pipework firmly in the pushfit connection. Please pay attention to ensure the correct connection to the inlet and the outlet.




5

Remove the cap seal from the cartridge and moisten the O-rings with water: push the cartridge up into the Filter Head/Bracket and turn it a ¼ turn to the right until locks into position.




6

When your Home Water Kit is installed, gently turn on the cold side of your tap and allow the cold water to flow through the cartridge for a minimum of 5 minutes. This allows the filter to activate & also rinses out any residue. Do not take any water during this time. During rinsing the water may contain black carbon particles. Keep rinsing until there are no particles left and the water is clear.



7

After rinsing, turn off your tap and double check the installation for any leakages.




Home Water Kit

Cartridge replacement


1

Close the water inlet/shut-off valve on the mains cold water supply under your sink. Turn on the cold side of your tap, allowing any residual water to empty from the pipework.




2

Turn the cartridge a ¼ turn to the left and gently pull downwards, away from the filter head/bracket, place towel or basin under filter to soak any water droplets.



3


Remove the cap seal on the replacement filter cartridge and moisten the o-rings with water: push the cartridge up and turn it a ¼ turn to the right.



4


Gently open the water inlet/shut-off valve and make sure to rinse the cartridge for 5 minutes. Do not take any water during this time.

During rinsing the water can obtain black carbon particles. Keep rinsing until there are no particles left and the water is clear.



5

After rinsing, turn off your tap and double-check your installation for any leakages.



elvion

elevate
your
water

Elvion is available at top
Builders Merchants nationwide.

www.elvionwater.co.uk
www.elvionwater.ie