



Barrel pump

SRL 355-955-18 l/min

Item number: 13 012
EAN: 4103810130120
Discount group: A

Technical data

Delivery rate (l/stroke): 0,3
 Delivery rate at 60 strokes/min (l/min): 18
 Pumping media: oils up to SAE 90
 Usage: container for 60 / 200 / 220 l
 Discharge: discharge spout, fastened by cap nut
 Length of suction tube (mm): 355
 Immersion depth (two-part) (mm): 355 - 625
 Immersion depth (three-part) (mm): 685 - 955
 Barrel screw coupling: G 2" male



Materials of parts in contact with liquid

Pump head: impact-resistant zinc die casting
 Pump body: aluminium
 Suction pipe: HDPE (high density polyethylene)
 Discharge rigid nozzle: PP
 Seals: PVC, NBR, FKM

Weight (kg): 1,45

Specification

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Ergonomic handle, non-slip, excellent power transfer and handling
- Packed in single carton box
- With EAN bar code

Special notes

- Suitable for use in conjunction with engine oil from SAE 5 W to SAE 50, gear oil from SAE 75 W to SAE 90, fuel oil, diesel, machine oil, cutting oil, petroleum, undiluted anti-freeze
- The ease of dismantling permits simple cleaning
- A suction strainer made of stainless steel can be easily installed without any tools in the suction tube
- The check valve prevents the fluid from flowing back into the container

Packaging

Dimensions LxWxH (mm): 800 x 90 x 90
 Weight including package (kg): 1,758
 Packing unit: 1,0

