



Ice Cube

CB 640 HC

B-Qube



Self-contained ice maker - Sprayer system Daily production up to 73 kg

Hotel	●	●	●	●	●	●	●	●	●
Restaurant	●	●	●	●	●	●	●	●	●
Fast food	●	●	●	●	●	●	●	●	●
Bar	●	●	●	●	●	●	●	●	●
Disco	●	●	●	●	●	●	●	●	●
Fish markets	●	●	●	●	●	●	●	●	●
Supermarkets	●	●	●	●	●	●	●	●	●
Medical & SPA	●	●	●	●	●	●	●	●	●
Industry	●	●	●	●	●	●	●	●	●

Hotel	●	●	●	●	●	●	●	●	●
Restaurant	●	●	●	●	●	●	●	●	●
Fast food	●	●	●	●	●	●	●	●	●
Bar	●	●	●	●	●	●	●	●	●
Disco	●	●	●	●	●	●	●	●	●
Fish markets	●	●	●	●	●	●	●	●	●
Supermarkets	●	●	●	●	●	●	●	●	●
Medical & SPA	●	●	●	●	●	●	●	●	●
Industry	●	●	●	●	●	●	●	●	●



Available Drain Pump (DP) version




Available Drain Pump (DP) version

► Features & Plus

- Compact and crystal cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- Adjustable Stainless Steel feet

- ON-OFF rocker switch
- Standard and special voltages
- HFC Free
- Automatic Washing system



Green-Tech Design




Side openings for better ventilation



Double water inlet (W models only)



Plug-in electrical connection



Drain Pump (DP)

2 Years Warranty subject to limitations

► Certifications available for this model



www.bremaice.it
info@bremaicegroup.it


We are Brema Group





Self-contained ice maker - Sprayer system

Daily production up to 73 kg



Installation




▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Available ice cube size



▶ Performances

Air temperature	Water temperature	Water temperature				
		7° C	45° F	15° C	60° F	21° C
10° C	73 kg					
50° F		161 lbs				
21° C			72 kg			
70° F				159 lbs		
32° C					62 kg	
90° F						137 lbs

▶ Connections standard version

- ① Water in.: 135 mm / 5 6/16" - 122 mm / 4 13/16" - 3/4"
- ② Water out.: 62 mm / 2 7/16" - 182 mm / 7 3/16" - 24 mm / 15/16"
- ③ Electrical connections: 100 mm / 3 15/16" - 252 mm / 9 15/16"
- ④* Cond. water in.: 124 mm / 4 14/16" - 208 mm / 8 3/16" - 3/4"

* Only for water cooling systems

Connections DP version

- 1 Water in.: 135 mm / 5 5/16" - 190 mm / 7 8/16" - 3/4"
- 2 Water out.: 72 mm / 2 13/16" - 51 mm / 2" - 24 mm / 15/16"
- 3 Electrical connection: 60 mm / 2 6/16" - 257 mm / 10 2/16"

All measures are referred to the rear bottom-left corner (L-H-Ø)

▶ Technical information

Production in 24h	72 kg / 159 lbs
Store capacity, up to	40 kg / 88 lbs
Cooling system	A - W
Kind of cube	A-18g, C-33g, D-13g, E-42g, Q-23g
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	590 W
Fuse	10 A
Electrical consumption	22 kWh/100kg

All the technical information must be considered at the following conditions:

Sizes without feet

Standard Cube (18 g)

Ambient temperature +21° C

Water temperature +15° C

Electrical consumption at +32° C (standard voltage)

Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Water consumption	A: 4 l/kg - 47,9 gal/100 lbs
	W: 16 l/kg - 191,7 gal/100 lbs
Sizes (L-P-H mm)	735 - 610 - 849
(L-P-H in)	28 15/16 - 24 - 33 7/16
Sizes with pack (L-P-H mm)	780 - 640 - 1015
(L-P-H in)	30 11/16 - 25 3/16 - 39 15/16
Net weight	67 kg / 148 lbs
Gross weight	79 kg / 174 lbs
Finish	Stainless steel, 18/8, scotch brite

Rev. 00 - Issued February 2026



We are Brema

