



Ice Cube

CB 840 HC

B-Qube



Self-contained ice maker - Sprayer system Daily production up to 82 kg

Hotel	●	●	●	●	●	●	●	●	●
Restaurant	●	●	●	●	●	●	●	●	●
Fast food	●	●	●	●	●	●	●	●	●
Bar	●	●	●	●	●	●	●	●	●
Disco	●	●	●	●	●	●	●	●	●
Fish markets	●	●	●	●	●	●	●	●	●
Supermarkets	●	●	●	●	●	●	●	●	●
Medical & SPA	●	●	●	●	●	●	●	●	●
Industry	●	●	●	●	●	●	●	●	●

Hotel	●	●	●	●	●	●	●	●	●
Restaurant	●	●	●	●	●	●	●	●	●
Fast food	●	●	●	●	●	●	●	●	●
Bar	●	●	●	●	●	●	●	●	●
Disco	●	●	●	●	●	●	●	●	●
Fish markets	●	●	●	●	●	●	●	●	●
Supermarkets	●	●	●	●	●	●	●	●	●
Medical & SPA	●	●	●	●	●	●	●	●	●
Industry	●	●	●	●	●	●	●	●	●



Available Drain Pump (DP) version



Available Drain Pump (DP) version

► Features & Plus

- Compact and crystal cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- Adjustable Stainless Steel feet

- ON-OFF rocker switch
- Standard and special voltages
- HFC Free
- Automatic Washing system



Green-Tech Design




Side openings for better ventilation



Double water inlet (W models only)



Plug-in electrical connection



Drain Pump (DP)

2 Years Warranty subject to limitations

► Certifications available for this model



www.bremaice.it
info@bremaicegroup.it


We are Brema Group





Self-contained ice maker - Sprayer system

Daily production up to 82 kg




▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Available ice cube size



▶ Performances

Air temperature	Water temperature	Water temperature				
		7° C	45° F	15° C	60° F	21° C
10° C	82 kg					
50° F		181 lbs				
21° C			80 kg			
70° F				176 lbs		
32° C					68 kg	
90° F						150 lbs

▶ Connections standard version

- ① Water in.: 135 mm / 5 5/16" - 237 mm / 9 5/16" - 3/4"
- ② Water out.: 62 mm / 2 7/16" - 242 mm / 9 8/16" - 24 mm / 15/16"
- ③ Electrical connections: 100 mm / 3 15/16" - 312 mm / 12 5/16"
- ④* Cond water in.: 98 mm / 3 14/16" - 177 mm / 6 15/16" - 3/4"

* Only for water cooling systems

Connections DP version

- 1 Water in.: 135 mm / 5 5/16" - 192 mm / 7 9/16" - 3/4"
- 2 Water out.: 72 mm / 2 13/16" - 53 mm / 2 1/16" - 24 mm / 15/16"
- 3 Electrical connection: 100 mm / 3 15/16" - 312 mm / 12 5/16"

All measures are referred to the rear bottom-left corner (L-H-Ø)

▶ Technical information

Production in 24h	80 kg / 176 lbs
Store capacity, up to	40 kg / 88 lbs
Cooling system	A - W
Kind of cube	A-18g, C-33g, D-13g, E-42g, Q-23g
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	700 W
Fuse	10 A
Electrical consumption	22 kWh/100kg

All the technical information must be considered at the following conditions:

- Sizes without feet
- Standard Cube (18 g)
- Ambient temperature +21° C
- Water temperature +15° C
- Electrical consumption at +32° C (standard voltage)
- Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Water consumption	A: 2,5 l/kg - 30 gal/100 lbs
	W: 14 l/kg - 167,8 gal/100 lbs
Sizes (L-P-H mm)	735 - 610 - 909
(L-P-H in)	28 15/16 - 24 - 35 13/16
Sizes with pack (L-P-H mm)	780 - 640 - 1085
(L-P-H in)	30 11/16 - 25 3/16 - 42 11/16
Net weight	71 kg / 157 lbs
Gross weight	83 kg / 183 lbs
Finish	Stainless steel, 18/8, scotch brite

Rev. 00 - Issued February 2026

